



## NICHE SHOWER IGLOOPRO ST 9 F IW 9 F N

Item number: 1450682

Quickly installed niche shower with a combination of a fixed screen and a hinged door in frosted glass. The shower solution is adapted for niche opening and is mounted between fixed walls. Easily installed and adjusted by one person, InstaQuick™. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. The door has lifting hinges so that it does not touch the floor when opened and is reversible. The shower rail can be fitted three ways: against the wall, against the ceiling or at an angle against the same wall as the shower. The door has 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. The screen has 8mm toughened safety glass and an extension profile can be purchased for surface-mounted piping. Height 2000 mm. 22 mm door seal, magnetic strip and handle included. The door can be supplemented with one or more extension profiles to be adapted to the dimensions of the niche.

25 year  
WARRANTY

Quality  
ISO 9001

InstaQuick™  
Hafa Pat. No. 308844

SundaHus

BRÄNDEGLER SÄKER VÄRDEBESKRIVNING  
FALÅN

Accepted  
monteringsanvisning  
2021:1

Listad i Svanens  
Husproduktportal

EPD

### DETAILED INFORMATION

| Item number                        |               | Material and surface treatment  |                        |
|------------------------------------|---------------|---------------------------------|------------------------|
| NOBB                               | 56920481      | Main material                   | Safety glass, Aluminum |
| RSK                                | 7329284       | Surface treatment               | Anodized               |
| EAN                                | 7330027116792 | Glass                           | Frosted glass          |
| Standards and classifications      |               | Color                           | Aluminum               |
| EN standard                        | EN14428       | Packaging dimensions and weight |                        |
| Sunda Hus                          | Yes           | Package width (m)               | 1,040                  |
| CE marked                          | Yes           | Package height(m)               | 2,080                  |
| ETIM                               | EC010962      | Package depth(m)                | 0,130                  |
| Product dimensions and weight      |               | Package weight(kg)              | 72,400                 |
| Height (mm)                        | 2000          |                                 |                        |
| Nische width                       | 1755-1785     |                                 |                        |
| Width door A                       | 885           |                                 |                        |
| Width of fixed wall (mm)           | 885           |                                 |                        |
| Glass thickness, door (mm)         | 6             |                                 |                        |
| Glass thickness, fixated wall (mm) | 8             |                                 |                        |
| Floor gap max. (mm)                | 8             |                                 |                        |
| Net weight (kg)                    | 68            |                                 |                        |
| Left/right model                   | Vändbar       |                                 |                        |

## CARE INSTRUCTIONS

---

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](https://hafa.eu)