Наға



SHOWER DOOR IGLOO PRO BEND 90 CLEAR BLACK

Item number: 1450326

Quickly installed curved shower door in clear glass. Practical shower door that is easily turned inwards when not in use and fits the smaller bathroom. The shower door is stable with a wall profile in black lacquered aluminum that can be mounted with a screw or glue trays. Easily installed and adjusted by one person, InstaQuick". The shower door has a lifting hinge so that it does not touch the floor when opening and is reversible. 6 mm toughened safety glass. Height 2000 mm. Can be mounted with surface-mounted pipes, cc 35 mm. 18 mm door seal and handle included.





Listad i Svanens Husproduktportal



DETAILED INFORMATION

Item number	
NOBB	57295363
RSK	7381723
EAN	7330027115511
Standards and classifications	
EN standard	EN14428
Säker Vatten	Yes
CE marked	Yes
ETIM	EC010038
Product dimensions and weight	
Height (mm)	2000
Width	737
Width max (mm)	747
Width min. (mm)	727
Depth (mm)	137
Glass thickness (mm)	6
Hinge lift height (mm)	4
Floor gap max. (mm)	8
Net weight (kg)	26
Left/right model	Vändbar

Material and surface treatment	
Main material	Safety glass, Aluminum
Surface treatment	Lacquered
Glass	Clear glass
Color	Black
Packaging dimensions and weight	
Package width (m)	0,810
Package height(m)	2,080
Package depth(m)	0,135
Package weight(kg)	28,000

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

Read more on hafa.eu