



SHOWER DOOR IGLOO PRO BEND 90 CLEAR BLACK

Item number: 1450326

Quickly installed curved shower door in clear glass. Practical shower door that is easily turned inwards when not in use and fits the smaller bathroom. The shower door is stable with a wall profile in black lacquered aluminum that can be mounted with a screw or glue trays. Easily installed and adjusted by one person, InstaQuick™. The shower door has a lifting hinge so that it does not touch the floor when opening and is reversible. 6 mm toughened safety glass. Height 2000 mm. Can be mounted with surface-mounted pipes, cc 35 mm. 18 mm door seal and handle included.

25 year
WARRANTY



Accepterad
monteringsanvisning
2021:1



Listad i Svanens
Husproduktportal



DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	57295363	Main material	Safety glass, Aluminum
RSK	7381723	Surface treatment	Lacquered
EAN	7330027115511	Glass	Clear glass
Standards and classifications		Color	Black
EN standard	EN14428	Packaging dimensions and weight	
Säker Vatten	Yes	Package width (m)	0,810
CE marked	Yes	Package height(m)	2,080
ETIM	EC010038	Package depth(m)	0,135
BVB id	164405	Package weight(kg)	28,000
EPD HUB id	HUB-2147		
Product dimensions and weight			
Height (mm)	2000		
Width	737		
Width max (mm)	747		
Width min. (mm)	727		
Depth (mm)	137		
Glass thickness (mm)	6		
Hinge lift height (mm)	4		
Floor gap max. (mm)	8		
Net weight (kg)	26		
Left/right model	Vändbar		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)