SHOWER WALL IGLOO PRO NICHE 2255-2285MM DOOR 100 + WALL

Item number: 1450649

Shower wall with a combination of a fixed screen and a hinged door in clear glass, mounted between walls. The shower solution is adapted for niche opening and is mounted between fixed walls. Easily installed and adjusted by one person, InstaQuick™. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. The door has lifting hinges so that it does not touch the floor when opened and is reversible. The shower rail can be fitted three ways: against the wall, against the ceiling or at an angle against the same wall as the shower. The door has 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. The screen has 8mm toughened safety glass and an extension profile can be purchased for surface-mounted piping. Height 2000 mm. 22 mm door seal, magnetic strip and handle included. For some widths, an extension profile is included. See measurements document. Floor gasket 18mm, magnet list and handle are included.

25 year WARRANTY

Accepterad monteringsanvisning 2021:1

Listad i Svanens Husproduktportal

DETAILED INFORMATION

Item number	
NOBB	56920356
RSK	7329271
EAN	7330027116662
Standards and classifications	
EN standard	EN14428
Sunda Hus	Yes
CE marked	Yes
ETIM	EC010962
Product dimensions and weight	
Height (mm)	2000
Nische width	2255-2285
Width door A	985
Width of fixed wall (mm)	1285
Glass thickness, door (mm)	6
Glass thickness, fixated wall (mm)	8
Floor gap max. (mm)	8
Net weight (kg)	89,2
Left/right model	Vändbar

Material and surface treatment	
Main material	Safety glass, Aluminum
Surface treatment	Anodized
Glass	Clear glass
Color	Aluminum
Packaging dimensions and weight	
Package width (m)	1,040
Package height(m)	2,080
Package depth(m)	0,130
Package weight(kg)	93,600

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

Read more on hafa.eu