



IGLOO PRO ROUND 70X100

Item number: 1450423

Quickly installed shower corner with curved doors in clear glass. When the shower is not in use the doors are easily turned inwards which frees up space in the bathroom. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. Easily installed and adjusted by one person, InstaQuick®. The shower doors have lifting hinges so that they do not touch the floor when opening and are reversible. 6 mm toughened safety glass. Height 2000 mm. Can be fitted with surface-mounted pipes, cc 35 mm. 22 mm door seal, magnetic strip and handles included.

25 year WARRANTY



Accepterad monteringsanvisning 2021:1



Listad i Svanens Husproduktportal

EPD

DETAILED INFORMATION

Item number

NOBB	53339372
RSK	7378906
EAN	7330027105437
Stocked article	Yes

Standards and classifications

EN standard	EN14428
Sunda Hus	Yes
Säker Vatten	Yes
CE marked	Yes
ETIM	EC010038
BVB id	119335

Product dimensions and weight

Height (mm)	2000
Width	700
Width max (mm)	710
Width min. (mm)	690
Depth (mm)	1000
Depth max. (mm)	1010
Depth min. (mm)	990
Glass thickness (mm)	6
Hinge lift height (mm)	4
Floor gap max. (mm)	8
Net weight (kg)	47
Left/right model	Vändbar

Material and surface treatment

Main material	Safety glass, Aluminum
Surface treatment	Anodized
Glass	Clear glass
Color	Aluminum

Packaging dimensions and weight

Package width (m)	0,915
Package height(m)	2,080
Package depth(m)	0,250
Package weight(kg)	51,000

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)