



IGLOO PRO SKÄRMVÄGG FROSTAT 130

Item number: 1450344

Elegant shower screen in frosted glass with large attractive glass surface for an airy and elegant impression, installed in the middle of the wall using two rails. The aluminum profile against wall and floor that makes the shower screen stable and keeps the water inside. The rail is 1200 mm and can be cut to any length. When buying width 1270 for mounting in corners, you need to buy an extra wall profile, 1450366. The shower screen can be combined with doors in the IglooPro series. Mounted with screw or glue trays. 8 mm toughened safety glass. Height 2000 mm.



Listad i Svanens
Husproduktportal



DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	53339205	Main material	Safety glass, Aluminum
RSK	7376773	Surface treatment	Anodized
EAN	7330027105246	Glass	Frosted glass
Stocked article	Yes	Color	Aluminum
Standards and classifications		Packaging dimensions and weight	
EN standard	EN14428	Package width (m)	1,340
Sunda Hus	Yes	Package height(m)	2,080
Säker Vatten	Yes	Package depth(m)	0,065
CE marked	Yes	Package weight(kg)	57,800
ETIM	EC010962	Miscellaneous	
Product dimensions and weight		Wall mounted	
Height (mm)	2000		
Width	1270		
Depth (mm)	21		
Glass thickness (mm)	8		
Net weight (kg)	55,8		
Left/right model	Vändbar		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.