



SHOWER DOOR IGLOO PRO 105 NICHE 1030-1070MM CLEAR

Item number: 1450603

Quickly installed straight shower door in clear glass with profiles in black matt or aluminum that is adapted for niche opening and is mounted between fixed walls. The shower door is stable with a wall profile and a profile for the magnetic strip in anodised aluminum. The wall profiles can be mounted with screws or glue trays. The shower door has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The shower door has a lifting hinge so that it does not touch the floor when opening and is reversible. 6 mm toughened safety glass. Height 2000 mm. Can be mounted with surface-mounted pipes, 35 mm. 22 mm trailer strip and handle included. The door can be supplemented with one or more extension profiles to be adapted to the dimensions of the niche.

25 year
WARRANTY

ISO 9001
Quality

InstaQuick™

SundaHus

SÄKER VATTENFALLNING

Accepted
monteringsanvisning
2021:1

Listad i Svanens
Husproduktportal

B

EPD

DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	53340624	Main material	Safety glass, Aluminum
RSK	7330645	Surface treatment	Anodized
EAN	7330027106687	Glass	Clear glass
Stocked article	Yes	Color	Aluminum
Standards and classifications		Packaging dimensions and weight	
EN standard	EN14428	Package width (m)	0,065
Sunda Hus	Yes	Package height(m)	2,100
Säker Vatten	Yes	Package depth(m)	1,100
CE marked	Yes	Package weight(kg)	37,000
ETIM	EC010962		
BVB id	185191		
Product dimensions and weight			
Height (mm)	2000		
Height min. (mm)	2000		
Width	1050		
Width max (mm)	1070		
Width min. (mm)	1030		
Depth (mm)	27		
Nische width	1030-1070		
Glass thickness (mm)	6		
Glass thickness, fixated wall (mm)	37		
Hinge lift height (mm)	4		
Floor gap max. (mm)	8		
Net weight (kg)	35		
Left/right model	Vändbar		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](https://hafa.eu)