



## IGLOO PRO CORNER 100X100

Item number: 1450449

Quickly installed shower corner with hinged doors in frosted glass. When the shower is not in use, the shower doors can be folded against the wall, which frees up space in the bathroom. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The door has lifting hinges so that it does not touch the floor when opened and is reversible. The doors have 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. Height 2000 mm. 22 mm door seal, magnetic strip and handle included.

25 year WARRANTY



Accepterad monteringsanvisning 2021:1

Listad i Svanens Husproduktportal



### DETAILED INFORMATION

#### Item number

NOBB	53339595
RSK	7378928
EAN	7330027105659
Stocked article	Yes

#### Standards and classifications

EN standard	EN14428
Sunda Hus	Yes
Säker Vatten	Yes
CE marked	Yes
ETIM	EC010034

#### Product dimensions and weight

Height (mm)	2000
Width	1000
Width max (mm)	1010
Width min. (mm)	990
Depth (mm)	1000
Depth max. (mm)	1010
Depth min. (mm)	990
Glass thickness (mm)	6
Hinge lift height (mm)	4
Floor gap max. (mm)	8
Net weight (kg)	65
Left/right model	Vändbar

#### Material and surface treatment

Main material	Safety glass, Aluminum
Surface treatment	Anodized
Glass	Frosted glass
Color	Aluminum

#### Packaging dimensions and weight

Package width (m)	1,040
Package height(m)	2,080
Package depth(m)	0,130
Package weight(kg)	69,000

## CARE INSTRUCTIONS

---

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)