



NICHE SHOWER DOUBLE IGLOOPRO 7X7 CLEAR N

Item number: 1450580

Quickly installed shower solution with two straight shower doors in clear glass. The shower solution is adapted for niche opening and is mounted between fixed walls. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. The doors have lifting hinges so that they do not touch the floor when opened and are reversible. 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. Height 2000 mm. 22 mm door seal, magnetic strip and handle included. The doors can be supplemented with one or more extension profiles to be adapted to the dimensions of the niche.

25 year
WARRANTY

ISO 9001
Quality

InstaQuick™
Hafa Pat. No. 310814



Accepterad
monteringsanvisning
2021:1

Listad i Svanens
Husproduktportal



DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	56919966	Main material	Safety glass, Aluminum
RSK	7329232	Surface treatment	Anodized
EAN	7330027116273	Glass	Clear glass
Standards and classifications		Color	Aluminum
EN standard	EN14428	Packaging dimensions and weight	
Sunda Hus	Yes	Package width (m)	0,740
CE marked	Yes	Package height(m)	2,080
ETIM	EC010962	Package depth(m)	0,130
Product dimensions and weight		Package weight(kg)	48,800
Height (mm)	2000		
Nische width	1350-1390		
Width door A	685		
Width door B	685		
Glass thickness (mm)	6		
Floor gap max. (mm)	8		
Net weight (kg)	44,8		
Left/right model	Vändbar		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.