



## SHOWER WALL IGLOO PRO I-WALL 100 CLEAR GLASS BLACK

Item number: 1450338

Elegant shower screen with aluminium profiles and fittings, and 8 mm clear tempered safety glass. Height 2000 mm. The shower screen can be installed in two ways: with one side against the wall or freestanding in the middle of the wall. Rails and wall profiles for both installation methods are included.

The shower screen is reversible, so you can choose which side to install it on. The shower screen can be combined with a shower curtain or with doors from the IglooPro series. For external pipework, an extension profile must be purchased separately. Installed with screws or adhesive. Add a rain shower set or shower set and a thermostatic mixer.

25 year  
WARRANTY



Listad i Svanens  
Husproduktportal



### DETAILED INFORMATION

<b>Item number</b>		<b>Material and surface treatment</b>	
NOBB	60049044	Main material	Safety glass, Aluminum
EAN	7330027147550	Glass	Clear glass
<b>Standards and classifications</b>		Color	Black
EN standard	EN14428	<b>Packaging dimensions and weight</b>	
CE marked	Yes	Package width (m)	1,040
ETIM	EC010962	Package height(m)	2,080
BVB id	162981	Package depth(m)	0,065
EPD HUB id	HUB-2147	Package weight(kg)	43,500
<b>Product dimensions and weight</b>			
Height (mm)	2000		
Height min. (mm)	2000		
Width	975		
Depth (mm)	21		
Glass thickness (mm)	8		
Net weight (kg)	41,5		

### CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.