



IGLOO PRO J + SKÄRMVÄGG FAST FROSTAT 80X90

Item number: 1450467

Quickly installed and extra spacious shower corner in J-shaped design that provides space for double shower sets. The shower corner consists of a J-shaped shower door in clear glass and a straight, fixed shower screen in frosted glass. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The doors have lifting hinges so that they do not touch the floor when opened and are reversible. The shower rail can be mounted in three different ways: against the wall, against the ceiling or at an angle to the same wall as the shower wall is mounted. The door has 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. The screen has 8mm toughened safety glass and an extension profile can be purchased for surface-mounted piping. Height 2000 mm. 22 mm door seal, magnetic strip and handle included.

25 year WARRANTY



Accepterad monteringsanvisning 2021:1



DETAILED INFORMATION

| | | | |
|--------------------------------------|---------------|--|------------------------|
| Item number | | Material and surface treatment | |
| NOBB | 53339765 | Main material | Safety glass, Aluminum |
| RSK | 7378945 | Surface treatment | Anodized |
| EAN | 7330027105826 | Glass | Clear glass/Frosted |
| Stocked article | Yes | Color | Aluminum |
| Standards and classifications | | Packaging dimensions and weight | |
| EN standard | EN14428 | Package width (m) | 0,985 |
| Sunda Hus | Yes | Package height(m) | 2,080 |
| Säker Vatten | Yes | Package depth(m) | 0,320 |
| CE marked | Yes | Package weight(kg) | 75,800 |
| ETIM | EC010038 | | |
| Product dimensions and weight | | | |
| Height (mm) | 2000 | | |
| Width | 1360 | | |
| Width max (mm) | 1370 | | |
| Width min. (mm) | 1355 | | |
| Depth (mm) | 800 | | |
| Depth max. (mm) | 810 | | |
| Depth min. (mm) | 790 | | |
| Glass thickness, door (mm) | 6 | | |
| Glass thickness, fixated wall (mm) | 8 | | |
| Hinge lift height (mm) | 4 | | |
| Floor gap max. (mm) | 8 | | |
| Net weight (kg) | 71,4 | | |
| Left/right model | Vändbar | | |

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)