



## IGLOO PRO DUSCHHÖRN / NISCHDUSCH FROSTAT 70X70

Item number: 1450520

Quickly installed shower corner with a fixed screen and a hinged door in frosted glass. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The door has lifting hinges so that it does not touch the floor when opened and is reversible. The shower rail can be fitted in three ways: against the wall, against the ceiling or at an angle against the same wall as the shower. The door has 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. The screen has 8mm toughened safety glass and an extension profile can be purchased for surface-mounted piping. Height 2000 mm. 22 mm door seal, magnetic strip and handle included.

25 year  
WARRANTY

Quality  
ISO 9001

InstaQuick™  
Patented solution for easy installation and adjustment



Accepterad  
monteringsanvisning  
2021:1

Listad i Svanens  
Husproduktportal



### DETAILED INFORMATION

<b>Item number</b>		<b>Material and surface treatment</b>	
NOBB	53339996	Main material	Safety glass, Aluminum
RSK	7378968	Surface treatment	Anodized
EAN	7330027106052	Glass	Frosted glass
Stocked article	Yes	Color	Aluminum
<b>Standards and classifications</b>		<b>Packaging dimensions and weight</b>	
EN standard	EN14428	Package width (m)	0,740
Sunda Hus	Yes	Package height(m)	2,080
Säker Vatten	Yes	Package depth(m)	0,130
CE marked	Yes	Package weight(kg)	55,800
ETIM	EC010034		
<b>Product dimensions and weight</b>			
Height (mm)	2000		
Width	700		
Width max (mm)	710		
Width min. (mm)	690		
Depth (mm)	700		
Depth max. (mm)	710		
Depth min. (mm)	695		
Width door A	685		
Width of fixed wall (mm)	685		
Glass thickness, door (mm)	6		
Glass thickness, fixated wall (mm)	8		
Hinge lift height (mm)	4		
Floor gap max. (mm)	8		
Net weight (kg)	51,4/2 (1450520)		
Left/right model	Vändbar		

## CARE INSTRUCTIONS

---

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)