



SHOWER CORNER IGLOO PRO FOLD 80X80 CLEAR

Item number: 1450623

Quickly installed shower corner in clear glass with integrated handles that folds in the middle to take up minimal space. Glueable profiles and easy to install and adjust thanks to the InstaQuick™ function. The shower doors have lifting hinges so that they do not touch the floor when opening and are reversible. Can be fitted with 12 mm surface mounted pipes, cc 35 mm. 6 mm toughened safety glass, height 2000 mm. 22 mm door seal included. The shower door can be combined with other doors and walls in the IglooPro series.



DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	56169434	Main material	Safety glass, Aluminum
RSK	7381675	Surface treatment	Anodized
EAN	7330027114682	Glass	Clear glass
Standards and classifications		Color	Aluminum
EN standard	EN14428	Packaging dimensions and weight	
CE marked	Yes	Package width (m)	0,480
ETIM	EC010034	Package height(m)	2,080
BVB id	129781	Package depth(m)	0,180
Product dimensions and weight		Package weight(kg)	55,000
Height (mm)	2000		
Width	800		
Width max (mm)	810		
Width min. (mm)	790		
Depth (mm)	800		
Depth max. (mm)	810		
Depth min. (mm)	790		
Glass thickness (mm)	6		
Hinge lift height (mm)	4		
Floor gap max. (mm)	8		
Net weight (kg)	50		
Left/right model	Vändbar		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](https://hafa.eu)