



## SHOWER CORNER IGLOO PRO DOOR + WALL CLEAR GLASS 100X100

Item number: 1450518

Quickly installed shower corner with a fixed screen and a hinged door in clear glass. The shower is stable with wall profiles in black lacquered aluminum that can be mounted with a screw or glue trays. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The door has lifting hinges so that it does not touch the floor when opened and is reversible. The shower rail can be fitted in three ways: against the wall, against the ceiling or at an angle against the same wall as the shower. The door has 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. The screen has 8mm toughened safety glass and an extension profile can be purchased for surface-mounted piping. Height 2000 mm. 22 mm door seal, magnetic strip and handle included.

25 year  
WARRANTY



Accepterad  
monteringsanvisning  
2021:1

Listad i Svanens  
Husproduktportal



### DETAILED INFORMATION

|                                      |                |  |                        |
|--------------------------------------|----------------|--|------------------------|
| <b>Item number</b>                   |                | <b>Material and surface treatment</b>  |                        |
| NOBB                                 | 53339977       | Main material                          | Safety glass, Aluminum |
| RSK                                  | 7378966        | Surface treatment                      | Anodized               |
| EAN                                  | 7330027106038  | Glass                                  | Clear glass            |
| Stocked article                      | Yes            | Color                                  | Aluminum               |
| <b>Standards and classifications</b> |                | <b>Packaging dimensions and weight</b> |                        |
| EN standard                          | EN14428        | Package width (m)                      | 1,040                  |
| Sunda Hus                            | Yes            | Package height(m)                      | 2,080                  |
| Säker Vatten                         | Yes            | Package depth(m)                       | 0,130                  |
| CE marked                            | Yes            | Package weight(kg)                     | 78,400                 |
| ETIM                                 | EC010034       |  |                        |
| <b>Product dimensions and weight</b> |                |  |                        |
| Height (mm)                          | 2000           |  |                        |
| Width                                | 1000           |  |                        |
| Width max (mm)                       | 1010           |  |                        |
| Width min. (mm)                      | 990            |  |                        |
| Depth (mm)                           | 1000           |  |                        |
| Depth max. (mm)                      | 1010           |  |                        |
| Depth min. (mm)                      | 995            |  |                        |
| Width door A                         | 985            |  |                        |
| Width of fixed wall (mm)             | 985            |  |                        |
| Glass thickness, door (mm)           | 6              |  |                        |
| Glass thickness, fixated wall (mm)   | 8              |  |                        |
| Hinge lift height (mm)               | 4              |  |                        |
| Floor gap max. (mm)                  | 8              |  |                        |
| Net weight (kg)                      | 74/2 (1450518) |  |                        |
| Left/right model                     | Vändbar        |  |                        |

## CARE INSTRUCTIONS

---

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)