



SHOWER CORNER IGLOO PRO DOOR + WALL CLEAR GLASS 90X80 ALU

Item number: 1450511

Quickly installed shower corner with a fixed screen and a hinged door in clear glass. The shower is stable with wall profiles in black lacquered aluminum that can be mounted with a screw or glue trays. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The door has lifting hinges so that it does not touch the floor when opened and is reversible. The shower rail can be fitted in three ways: against the wall, against the ceiling or at an angle against the same wall as the shower. The door has 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. The screen has 8mm toughened safety glass and an extension profile can be purchased for surface-mounted piping. Height 2000 mm. 22 mm door seal, magnetic strip and handle included.

25 year
WARRANTY



Accepterad
monteringsanvisning
2021:1

Listad i Svanens
Husproduktportal



DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	53339905	Main material	Safety glass, Aluminum
RSK	7378959	Surface treatment	Anodized
EAN	7330027105963	Glass	Clear glass
Stocked article	Yes	Color	Aluminum
Standards and classifications		Packaging dimensions and weight	
EN standard	EN14428	Package width (m)	0,940
Sunda Hus	Yes	Package height(m)	2,080
Säker Vatten	Yes	Package depth(m)	0,130
CE marked	Yes	Package weight(kg)	67,600
ETIM	EC010034		
Product dimensions and weight			
Height (mm)	2000		
Width	900		
Width max (mm)	910		
Width min. (mm)	890		
Depth (mm)	800		
Depth max. (mm)	810		
Depth min. (mm)	795		
Width door A	885		
Width of fixed wall (mm)	785		
Glass thickness, door (mm)	6		
Glass thickness, fixated wall (mm)	8		
Hinge lift height (mm)	4		
Floor gap max. (mm)	8		
Net weight (kg)	63,2/2 (1450511)		
Left/right model	Vändbar		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](https://hafa.eu)