



SHOWER DOOR IGLOO PRO FOLD

Item number: 1450612

Quickly installed and foldable shower door with clear glass that is adapted for niche opening. Integrated handle that folds in the middle to take up minimal space and makes it possible to create a smart shower solution for the small bathroom. The folding door can easily be folded against the wall when not in use and creates a practical shower solution even if the toilet or bathroom furniture is located near the shower. The shower door is stable with a wall profile in anodised aluminum that can be mounted with a screw or glue trays. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The shower door has a lifting hinge so that it does not touch the floor when opening and is reversible. The shower door can be combined with other doors and screens in the IglooPro series. 6 mm toughened safety glass. Height 2000 mm. Can be mounted with surface-mounted pipes, 35 mm. 22 mm door seal included. Integrated handle. For some widths, an extension profile is included. See measurements document. Floor gasket 18mm and magnet list are included.

25 year WARRANTY

Swedish quality since 1962
Quality

InstaQuick™
Pat. No. 333885



Listad i Svanens
Husproduktportal



DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	56169396	Main material	Safety glass, Aluminum
RSK	7333885	Surface treatment	Anodized
EAN	7330027114644	Glass	Clear glass
		Color	Aluminum
Standards and classifications		Packaging dimensions and weight	
EN standard	EN14428	Package width (m)	0,630
CE marked	Yes	Package height(m)	2,080
ETIM	EC010962	Package depth(m)	0,090
BVB id	129781	Package weight(kg)	32,500
Product dimensions and weight			
Height (mm)	2000		
Width	950		
Width max (mm)	970		
Width min. (mm)	930		
Depth (mm)	27		
Nische width	930-970		
Glass thickness (mm)	6		
Hinge lift height (mm)	4		
Floor gap max. (mm)	8		
Net weight (kg)	31,5		
Left/right model	Vändbar		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)