

SHOWER DOOR IGLOO PRO 95 NICHE 930-1000MM CLEAR GLASS

Item number: 1450864

Quickly installed straight shower door in clear glass with profiles in black matt or aluminum that is adapted for niche opening and is mounted between fixed walls. The shower door is stable with a wall profile and a profile for the magnetic strip in anodised aluminum. The wall profiles can be mounted with screws or glue trays. The shower door has a patented solution for easy installation and adjustment, Hafa's InstaQuick ™. The shower door has a lifting hinge so that it does not touch the floor when opening and is reversible. 6 mm toughened safety glass. Height 2000 mm. Can be mounted with surface-mounted pipes, 35 mm. 22 mm trailer strip and handle included. The door can be supplemented with one or more extension profiles to be adapted to the dimensions of the niche.

25 year WARRANTY

Quality

InstaQuick™

EPD

DETAILED INFORMATION

Item number	
NOBB	60049072
EAN	7330027149509
Standards and classifications	
EN standard	EN14428
CE marked	Yes
ETIM	EC011329
Product dimensions and weight	
Height (mm)	2000
Height min. (mm)	2000
Width	980
Width max (mm)	1000
Width min. (mm)	960
Depth (mm)	27
Nische width	960-1000
Glass thickness (mm)	6
Glass thickness, fixated wall (mm)	35.8
Net weight (kg)	35,3

Material and surface treatment	
Main material	Safety glass, Aluminum
Surface treatment	Anodized
Glass	Clear glass
Color	Aluminum
Packaging dimensions and weight	
Package width (m)	0,940
Package height(m)	2,080
Package depth(m)	0,118
Package weight(kg)	35,800

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.