



SHOWER DOOR IGLOO PRO FOLD 80 CLEAR

Item number: 1450306

Shower enclosure with foldable doors in clear glass that can free up space and make it possible with a smart solution for the small bathroom where it can be difficult to fit a traditional corner enclosure. The foldable door can easily be folded into the wall when not in use and creates a practical solution also for when toilet or bathroom furniture is close to the shower area. The shower corner is sturdy with wall profiles in eloxated or black painted aluminum that can be mounted with screws or using glue plates. The corner has a patent filed solution for easy installation and adjustment, Hafa's InstaQuick™. The doors has lifting function to ensure the do not collide with the floor when opened and are reversible so you can choose what wall to mount onto. The shower door can be combined with other components in the IglooPro series. 6 mm safety glass. Height 2000 mm. Can be mounted where visible piping is present, 35 mm. 22 mm gasket, magnet enclosure and integrated handles are included.

25 year
WARRANTY

Swedish quality since 1902
Quality

Hafa Pat. No. 313834
InstaQuick™



Accepterad
monteringsanvisning
2021:1



Listad i Svanens
Husproduktportal



DETAILED INFORMATION

Item number

NOBB	56169358
RSK	7333881
EAN	7330027114309

Standards and classifications

EN standard	EN14428
CE marked	Yes
ETIM	EC010962
BVB id	129781
EPD HUB id	HUB-2147

Product dimensions and weight

Height (mm)	2000
Width	775
Width max (mm)	785
Width min. (mm)	765
Depth (mm)	27
Glass thickness (mm)	6
Hinge lift height (mm)	4
Floor gap max. (mm)	8
Net weight (kg)	25
Left/right model	Vändbar

Material and surface treatment

Main material	Safety glass, Aluminum
Surface treatment	Anodized
Glass	Clear glass
Color	Aluminum

Packaging dimensions and weight

Package width (m)	0,480
Package height(m)	2,080
Package depth(m)	0,090
Package weight(kg)	27,500

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)