



SHOWER DOOR IGLOO PRO STR CLEAR GLASS 80 ALUMINIUM

Item number: 1450301

Quickly installed straight shower door in clear glass with profiles in black matt or aluminum. Practical reversible shower door that is easily turned inwards when not in use and fits the smaller bathroom. The shower door is stable with a wall profile in black lacquered aluminum that can be mounted with a screw or glue trays. Easily installed and adjusted by one person, InstaQuick™. The shower door has a lifting hinge so that it does not touch the floor when opening and is reversible. The shower door can be combined with other doors and screens in the IglooPro series. 6 mm toughened safety glass. Height 2000 mm. Can be mounted with surface-mounted pipes, cc 35 mm. 22 mm door seal and handle included.



DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	53338997	Main material	Safety glass, Aluminum
RSK	7330630	Surface treatment	Anodized
EAN	7330027105031	Glass	Clear glass
Stocked article	Yes	Color	Aluminum
Standards and classifications		Packaging dimensions and weight	
EN standard	EN14428	Package width (m)	0,840
Sunda Hus	Yes	Package height(m)	2,080
Säker Vatten	Yes	Package depth(m)	0,065
CE marked	Yes	Package weight(kg)	28,400
ETIM	EC010962		
BVB id	119335		
EPD HUB id	HUB-2147		
Product dimensions and weight			
Height (mm)	2000		
Width	775		
Width max (mm)	785		
Width min. (mm)	765		
Depth (mm)	27		
Glass thickness (mm)	6		
Hinge lift height (mm)	4		
Floor gap max. (mm)	8		
Net weight (kg)	26,4		
Left/right model	Vändbar		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)