

SHOWER DOOR IGLOO PRO STR 100 CLEAR GLASS BLACK

Item number: 1450317

Quickly installed straight shower door in clear glass with prodiles in black matt or aluminum. Practical reversible shower door that is easily turned inwards when not in use and fits the smaller bathroom. The shower door is stable with a wall profile in black lacquered aluminum that can be mounted with a screw or glue trays. Easily installed and adjusted by one person, InstaQuick™. The shower door has a lifting hinge so that it does not touch the floor when opening and is reversible. The shower door can be combined with other doors and screens in the IglooPro series. 6 mm toughened safety glass. Height 2000 mm. Can be mounted with surface-mounted pipes, cc 35 mm. 22 mm door seal and handle included.

25 year WARRANTY

Listad i Svanens Husprodukt portal

EPD

DETAILED INFORMATION

Item number	
NOBB	60049028
EAN	7330027147581
Standards and classifications	
EN standard	EN14428
CE marked	Yes
ETIM	EC010962
BVB id	164405
EPD HUB id	HUB-2147
Product dimensions and weight	
Height (mm)	2000
Width	975
Width max (mm)	985
Width min. (mm)	965
Depth (mm)	27
Glass thickness (mm)	6
Hinge lift height (mm)	4
Floor gap max. (mm)	8
Net weight (kg)	32,5
Left/right model	Vändbar

Material and surface treatment	
Main material	Safety glass, Aluminum
Surface treatment	Lacquered
Glass	Clear glass
Color	Black
Packaging dimensions and weight	
Package width (m)	1,040
Package height(m)	2,080
Package depth(m)	0,065
Package weight(kg)	34,500

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

Read more on hafa.eu