



SHOWER WALL IGLOO PRO NICHE 1755-1785MM DOOR 100 + WALL

Item number: 1450646

Shower wall with a combination of a fixed screen and a hinged door in clear glass, mounted between walls. The shower solution is adapted for niche opening and is mounted between fixed walls. Easily installed and adjusted by one person, InstaQuick™. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. The door has lifting hinges so that it does not touch the floor when opened and is reversible. The shower rail can be fitted three ways: against the wall, against the ceiling or at an angle against the same wall as the shower. The door has 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. The screen has 8mm toughened safety glass and an extension profile can be purchased for surface-mounted piping. Height 2000 mm. 22 mm door seal, magnetic strip and handle included. For some widths, an extension profile is included. See measurements document. Floor gasket 18mm, magnet list and handle are included.

25 year
WARRANTY

Quality
Guarantee

InstaQuick™
No. 308544

SundaHus

BRÄNDEGLER SÄKER VÄRDESKALKYLLATION

Accepted
monteringsanvisning
2021:1

Listad i Svanens
Husproduktportal

DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	56920322	Main material	Safety glass, Aluminum
RSK	7329268	Surface treatment	Anodized
EAN	7330027116631	Glass	Clear glass
		Color	Aluminum
Standards and classifications		Packaging dimensions and weight	
EN standard	EN14428	Package width (m)	1,040
Sunda Hus	Yes	Package height(m)	2,080
CE marked	Yes	Package depth(m)	0,130
ETIM	EC010962	Package weight(kg)	69,700
Product dimensions and weight			
Height (mm)	2000		
Nische width	1755-1785		
Width door A	985		
Width of fixed wall (mm)	785		
Glass thickness, door (mm)	6		
Glass thickness, fixated wall (mm)	8		
Floor gap max. (mm)	8		
Net weight (kg)	63		
Left/right model	Vändbar		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](https://hafa.eu)