



SHOWER WALL IGLOO PRO I-WALL 130 CLEAR GLASS ALUMINIUM

Item number: 1450334

Elegant shower screen with aluminium profiles and fittings, and 8 mm clear tempered safety glass. Height 2000 mm. The shower screen can be installed in two ways: with one side against the wall or freestanding in the middle of the wall. Rails and wall profiles for both installation methods are included.

The shower screen is reversible, so you can choose which side to install it on. The shower screen can be combined with a shower curtain or with doors from the IglooPro series. For external pipework, an extension profile must be purchased separately. Installed with screws or adhesive. Add a rain shower set or shower set and a thermostatic mixer.



Listad i Svanens
Husproduktportal



DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	53339156	Main material	Safety glass, Aluminum
RSK	7376768	Surface treatment	Anodized
EAN	7330027105192	Glass	Clear glass
Stocked article	Yes	Color	Aluminum
Standards and classifications		Packaging dimensions and weight	
EN standard	EN14428	Package width (m)	1,340
Sunda Hus	Yes	Package height(m)	2,080
Säker Vatten	Yes	Package depth(m)	0,065
CE marked	Yes	Package weight(kg)	57,800
ETIM	EC010962	Miscellaneous	
BVB id	117708	Wall mounted	
EPD HUB id	HUB-2147		
Product dimensions and weight			
Height (mm)	2000		
Height min. (mm)	2000		
Width	1270		
Depth (mm)	1200		
Glass thickness (mm)	8		
Net weight (kg)	55,8		
Left/right model	Vändbar		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)