



IGLOO PRO J + SKÄRMVÄGG FAST KLARGLAS 80X90

Item number: 1450462

Quickly installed and extra spacious shower corner in J-shaped design that provides space for double shower sets. The shower corner consists of a J-shaped shower door and a straight shower screen in clear glass. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The door has lifting hinges so that it does not touch the floor when opened and is reversible. The shower rail can be fitted in three ways: against the wall, against the ceiling or at an angle against the same wall as the shower. The door has 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. The screen has 8mm toughened safety glass and an extension profile can be purchased for surface-mounted piping. Height 2000 mm. 22 mm door seal, magnetic strip and handle included.

25 year WARRANTY



Accepterad monteringsanvisning 2021:1



DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	53339716	Main material	Safety glass, Aluminum
RSK	7378940	Surface treatment	Anodized
EAN	7330027105772	Color	Aluminum
Stocked article	Yes	Packaging dimensions and weight	
Standards and classifications		Package width (m)	0,985
EN standard	EN14428	Package height(m)	2,080
Sunda Hus	Yes	Package depth(m)	0,320
Säker Vatten	Yes	Package weight(kg)	75,800
CE marked	Yes		
ETIM	EC010038		
Product dimensions and weight			
Height (mm)	2000		
Width	1360		
Width max (mm)	1370		
Width min. (mm)	1355		
Depth (mm)	800		
Depth max. (mm)	810		
Depth min. (mm)	790		
Glass thickness, door (mm)	6		
Glass thickness, fixated wall (mm)	8		
Hinge lift height (mm)	4		
Floor gap max. (mm)	8		
Net weight (kg)	71,4		
Left/right model	Vändbar		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)