



## NICHE SHOWER DOUBLE IGLOOPRO 8X8 CLEAR N

Item number: 1450584

Quickly installed shower solution with two straight shower doors in clear glass. The shower solution is adapted for niche opening and is mounted between fixed walls. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. The doors have lifting hinges so that they do not touch the floor when opened and are reversible. 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. Height 2000 mm. 22 mm door seal, magnetic strip and handle included. The doors can be supplemented with one or more extension profiles to be adapted to the dimensions of the niche.

25 year  
WARRANTY

Swedish quality since 1967  
Quality

Hafa Pat. No. 3108544  
InstaQuick™



Accepterad  
monteringsanvisning  
2021:1

Listad i Svanens  
Husproduktportal



### DETAILED INFORMATION

| Item number                   |               | Material and surface treatment  |                        |
|-------------------------------|---------------|---------------------------------|------------------------|
| NOBB                          | 56920004      | Main material                   | Safety glass, Aluminum |
| RSK                           | 7329236       | Surface treatment               | Anodized               |
| EAN                           | 7330027116310 | Glass                           | Clear glass            |
| Standards and classifications |               | Color                           | Aluminum               |
| EN standard                   | EN14428       | Packaging dimensions and weight |                        |
| Sunda Hus                     | Yes           | Package width (m)               | 0,940                  |
| CE marked                     | Yes           | Package height(m)               | 2,080                  |
| ETIM                          | EC010962      | Package depth(m)                | 0,130                  |
| Product dimensions and weight |               | Package weight(kg)              | 56,800                 |
| Height (mm)                   | 2000          |                                 |                        |
| Nische width                  | 1550-1590     |                                 |                        |
| Width door A                  | 785           |                                 |                        |
| Width door B                  | 785           |                                 |                        |
| Glass thickness (mm)          | 6             |                                 |                        |
| Floor gap max. (mm)           | 8             |                                 |                        |
| Net weight (kg)               | 52,8          |                                 |                        |
| Left/right model              | Vändbar       |                                 |                        |

### CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.