



## IGLOO PRO DUSCHHÖRN / NISCHDUSCH FROSTAT/KLARGLAS

Item number: 1450573

Quickly installed shower corner with a hinged door in frosted glass and a fixed screen in clear glass. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The door has lifting hinges so that it does not touch the floor when opened and is reversible. The shower rail can be fitted in three ways: against the wall, against the ceiling or at an angle against the same wall as the shower. The door has 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. The screen has 8mm toughened safety glass and an extension profile can be purchased for surface-mounted piping. Height 2000 mm. 22 mm door seal, magnetic strip and handle included.

25 year  
WARRANTY

Quality  
ISO 9001

InstaQuick™  
Hafa Pat. No. 308844

SundaHus

BRANSCHENS SÄKER VÄRDESKALIFIKATION

Accepted  
monteringsanvisning  
2021:1

EPD

### DETAILED INFORMATION

| Item number                        |                      | Material and surface treatment  |                        |
|------------------------------------|----------------------|---------------------------------|------------------------|
| NOBB                               | 53340522             | Main material                   | Safety glass, Aluminum |
| RSK                                | 7379021              | Surface treatment               | Anodized               |
| EAN                                | 7330027106588        | Glass                           | Frosted/Clear glass    |
| Stocked article                    | Yes                  | Color                           | Aluminum               |
| Standards and classifications      |                      | Packaging dimensions and weight |                        |
| EN standard                        | EN14428              | Package width (m)               | 1,040                  |
| Sunda Hus                          | Yes                  | Package height(m)               | 2,080                  |
| Säker Vatten                       | Yes                  | Package depth(m)                | 0,130                  |
| CE marked                          | Yes                  | Package weight(kg)              | 76,300                 |
| ETIM                               | EC010034             |                                 |                        |
| Product dimensions and weight      |                      |                                 |                        |
| Height (mm)                        | 2000                 |                                 |                        |
| Width                              | 900                  |                                 |                        |
| Width max (mm)                     | 910                  |                                 |                        |
| Depth (mm)                         | 1000                 |                                 |                        |
| Depth max. (mm)                    | 1010                 |                                 |                        |
| Depth min. (mm)                    | 995                  |                                 |                        |
| Width door A                       | 885                  |                                 |                        |
| Width of fixed wall (mm)           | 985                  |                                 |                        |
| Glass thickness, door (mm)         | 6                    |                                 |                        |
| Glass thickness, fixated wall (mm) | 8                    |                                 |                        |
| Hinge lift height (mm)             | 4                    |                                 |                        |
| Floor gap max. (mm)                | 8                    |                                 |                        |
| Net weight (kg)                    | 71,9                 |                                 |                        |
| Left/right model                   | Vändbar /2 (1450573) |                                 |                        |

## CARE INSTRUCTIONS

---

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](https://hafa.eu)