



IGLOO PRO SKÄRMVÄGG RAK FROSTAT 90

Item number: 1450312

Quickly installed straight shower door with frosted glass. Practical reversible shower door that is easily turned inwards when not in use and fits the smaller bathroom. The shower door is stable with a wall profile in anodised aluminum that can be mounted with a screw or glue trays. Easily installed and adjusted by one person, InstaQuick™. The shower door has a lifting hinge so that it does not touch the floor when opening and is reversible. The shower door can be combined with other doors and screens in the IglooPro series. 6 mm toughened safety glass. Height 2000 mm. Can be mounted with 12 mm surface-mounted pipes, cc 35 mm. 22 mm door seal and handle included.



Accepterad
monteringsanvisning
2021:1

Listad i Svanens
Husproduktportal



DETAILED INFORMATION

Item number

NOBB	53339046
RSK	7330635
EAN	7330027105086
Stocked article	Yes

Standards and classifications

EN standard	EN14428
Sunda Hus	Yes
Säker Vatten	Yes
CE marked	Yes
ETIM	EC010962
EPD HUB id	HUB-2147

Product dimensions and weight

Height (mm)	2000
Width	875
Width max (mm)	885
Width min. (mm)	865
Depth (mm)	27
Glass thickness (mm)	6
Hinge lift height (mm)	4
Floor gap max. (mm)	8
Net weight (kg)	30,4
Left/right model	Vändbar

Material and surface treatment

Main material	Safety glass, Aluminum
Surface treatment	Anodized
Glass	Frosted glass
Color	Aluminum

Packaging dimensions and weight

Package width (m)	0,940
Package height(m)	2,080
Package depth(m)	0,065
Package weight(kg)	32,400

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)