



## IGLOO PRO CORNER 70X90

Item number: 1450442

Quickly installed shower corner with hinged doors in frosted glass. When the shower is not in use, the shower doors can be folded against the wall, which frees up space in the bathroom. The shower is stable with wall profiles in anodized aluminum that can be mounted with a screw or glue trays. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The door has lifting hinges so that it does not touch the floor when opened and is reversible. The doors have 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. Height 2000 mm. 22 mm door seal, magnetic strip and handle included.



Accepterad  
monteringsanvisning  
2021:1

Listad i Svanens  
Husproduktportal



### DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	53339523	Main material	Safety glass, Aluminum
RSK	7378921	Surface treatment	Anodized
EAN	7330027105581	Glass	Frosted glass
Stocked article	Yes	Color	Aluminum
Standards and classifications		Packaging dimensions and weight	
EN standard	EN14428	Package width (m)	0,940
Sunda Hus	Yes	Package height(m)	2,080
Säker Vatten	Yes	Package depth(m)	0,130
CE marked	Yes	Package weight(kg)	56,800
ETIM	EC010034		
Product dimensions and weight			
Height (mm)	2000		
Width	700		
Width max (mm)	710		
Width min. (mm)	690		
Depth (mm)	900		
Depth max. (mm)	910		
Depth min. (mm)	890		
Glass thickness (mm)	6		
Hinge lift height (mm)	4		
Floor gap max. (mm)	8		
Net weight (kg)	52,8		
Left/right model	Vändbar		

## CARE INSTRUCTIONS

---

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](https://hafa.eu)