



SHOWER WALL IGLOO PRO NICHE 2155-2185MM DOOR 90 + WALL

Item number: 1450644

Shower wall with a combination of a fixed screen and a hinged door in clear glass, mounted between walls. The shower solution is adapted for niche opening and is mounted between fixed walls. Easily installed and adjusted by one person, InstaQuick®. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. The door has lifting hinges so that it does not touch the floor when opened and is reversible. The shower rail can be fitted three ways: against the wall, against the ceiling or at an angle against the same wall as the shower. The door has 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. The screen has 8mm toughened safety glass and an extension profile can be purchased for surface-mounted piping. Height 2000 mm. 22 mm door seal, magnetic strip and handle included. For some widths, an extension profile is included. See measurements document. Floor gasket 18mm, magnet list and handle are included.

25 year
WARRANTY

Quality
ISO 9001

InstaQuick®
Hafa Pat. No. 318814

SundaHus®

BRÄNDEGLER SÄKER VÄRDEBESKÄDNING

Accepted
monteringsanvisning
2021:1

Listad i Svanens
Husproduktportal

DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	56920303	Main material	Safety glass, Aluminum
RSK	7329266	Surface treatment	Anodized
EAN	7330027116617	Glass	Clear glass
Standards and classifications		Color	Aluminum
EN standard	EN14428	Packaging dimensions and weight	
Sunda Hus	Yes	Package width (m)	1,040
CE marked	Yes	Package height(m)	2,080
ETIM	EC010962	Package depth(m)	0,130
Product dimensions and weight		Package weight(kg)	91,500
Height (mm)	2000		
Nische width	2155-2185		
Width door A	885		
Width of fixed wall (mm)	1285		
Glass thickness, door (mm)	6		
Glass thickness, fixated wall (mm)	8		
Floor gap max. (mm)	8		
Net weight (kg)	87,1		
Left/right model	Vändbar		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](https://hafa.eu)