



SHOWER WALL IGLOO PRO I-WALL 130 CLEAR GLASS BLACK

Item number: 1450339

Elegant shower screen with aluminium profiles and fittings, and 8 mm clear tempered safety glass. Height 2000 mm. The shower screen can be installed in two ways: with one side against the wall or freestanding in the middle of the wall. Rails and wall profiles for both installation methods are included.

The shower screen is reversible, so you can choose which side to install it on. The shower screen can be combined with a shower curtain or with doors from the IglooPro series. For external pipework, an extension profile must be purchased separately. Installed with screws or adhesive. Add a rain shower set or shower set and a thermostatic mixer.

25 year
WARRANTY



Listad i Svanens
Husproduktportal



DETAILED INFORMATION

| | | | |
|--------------------------------------|---------------|--|------------------------|
| Item number | | Material and surface treatment | |
| NOBB | 60049041 | Main material | Safety glass, Aluminum |
| EAN | 7330027147567 | Glass | Clear glass |
| Standards and classifications | | Color | Black |
| EN standard | EN14428 | Packaging dimensions and weight | |
| CE marked | Yes | Package width (m) | 1,340 |
| ETIM | EC010962 | Package height(m) | 2,080 |
| BVB id | 162981 | Package depth(m) | 0,065 |
| EPD HUB id | HUB-2147 | Package weight(kg) | 57,800 |
| Product dimensions and weight | | | |
| Height (mm) | 2000 | | |
| Height min. (mm) | 2000 | | |
| Width | 1270 | | |
| Depth (mm) | 1200 | | |
| Glass thickness (mm) | 8 | | |
| Net weight (kg) | 55,8 | | |

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.