

SHOWER WALL IGLOO PRO I-WALL 130 CLEAR GLASS BLACK

Item number: 1450339

Elegant shower screen with aluminium profiles and fittings, and 8 mm clear tempered safety glass. Height 2000 mm. The shower screen can be installed in two ways: with one side against the wall or freestanding in the middle of the wall. Rails and wall profiles for both installation methods are included.

The shower screen is reversible, so you can choose which side to install it on. The shower screen can be combined with a shower curtain or with doors from the IglooPro series. For external pipework, an extension profile must be purchased separately. Installed with screws or adhesive. Add a rain shower set or shower set and a thermostatic mixer.

25 year WARRANTY

Quality

B

Listad i Svanens Husprodukt portal

EPD

DETAILED INFORMATION

Item number	
NOBB	60049041
EAN	7330027147567
Standards and classifications	
EN standard	EN14428
CE marked	Yes
ETIM	EC010962
BVB id	162981
EPD HUB id	HUB-2147
Product dimensions and weight	
Height (mm)	2000
Height min. (mm)	2000
Width	1270
Depth (mm)	1200
Glass thickness (mm)	8
Net weight (kg)	55,8

Material and surface treatment	
Main material	Safety glass, Aluminum
Glass	Clear glass
Color	Black
Packaging dimensions and weight	
Package width (m)	1,340
Package height(m)	2,080
Package depth(m)	0,065
Package weight(kg)	57,800

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.