

NEW IGLOO R 90ST

Item number: 1471000

Elegant shower corner with curved doors in clear glass. When the shower is not in use the doors are easily turned inwards which frees up space in the bathroom. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. Easily installed and adjusted by one person, InstaQuick™. The shower doors have lifting hinges so that they do not touch the floor when opening and are reversible. 6 mm toughened safety glass. Height 2000 mm. Can be fitted with surface-mounted pipes, cc 35 mm. 18 mm door seal, magnetic strip and handles included.

DETAILED INFORMATION

Item number	
NOBB	40793663
RSK	7340638
EAN	7330027017754
Stocked article	Yes
Standards and classifications	
EN standard	EN14428
Sunda Hus	Yes
CE marked	Yes
ETIM	EC010038
Product dimensions and weight	
Height (mm)	2000
Width	900
Depth (mm)	900
Right door width	910
Left door width	910
Glass thickness (mm)	6
Hinge lift height (mm)	5
Floor gap max. (mm)	11
Net weight (kg)	48

Material and surface treatment	
Surface treatment	Anodized
Glass	Clear glass
Color	Silver
Packaging dimensions and weight	
Package width (m)	0,800
Package height(m)	0,170
Package depth(m)	2,000
Package weight(kg)	48,500

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

Read more on hafa.eu