



IGLOO PRO DUSCHHÖRN / NISCHDUSCH FROSTAT/KLARGLAS

Item number: 1450561

Quickly installed shower corner with a hinged door in frosted glass and a fixed screen in clear glass. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The door has lifting hinges so that it does not touch the floor when opened and is reversible. The shower rail can be fitted in three ways: against the wall, against the ceiling or at an angle against the same wall as the shower. The door has 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. The screen has 8mm toughened safety glass and an extension profile can be purchased for surface-mounted piping. Height 2000 mm. 22 mm door seal, magnetic strip and handle included.

25 year
WARRANTY



Accepterad
monteringsanvisning
2021:1



DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	53340401	Main material	PU reinforced acrylic, Cast marble, Steel, Brass, Glass, Safety glass, Aluminum
RSK	7379009	Surface treatment	Anodized
EAN	7330027106465	Glass	Frosted/Clear glass
Stocked article	Yes	Color	Aluminum
Standards and classifications		Packaging dimensions and weight	
EN standard	EN14428	Package width (m)	0,840
Sunda Hus	Yes	Package height(m)	2,080
Säker Vatten	Yes	Package depth(m)	0,130
CE marked	Yes	Package weight(kg)	59,600
ETIM	EC010034		
Product dimensions and weight			
Height (mm)	2000		
Width	700		
Width max (mm)	710		
Width min. (mm)	690		
Depth (mm)	800		
Depth max. (mm)	810		
Depth min. (mm)	795		
Width door A	685		
Width of fixed wall (mm)	785		
Glass thickness, door (mm)	6		
Glass thickness, fixated wall (mm)	8		
Hinge lift height (mm)	4		
Floor gap max. (mm)	8		
Net weight (kg)	55,2/2 (1450561)		
Left/right model	Vändbar		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)