IGLOO PRO J + SKÄRMVÄGG FAST KLARGLAS 80X100

Item number: 1450463

Quickly installed and extra spacious shower corner in J-shaped design that provides space for double shower sets. The shower corner consists of a J-shaped shower door and a straight shower screen in clear glass. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick ™. The door has lifting hinges so that it does not touch the floor when opened and is reversible. The shower rail can be fitted in three ways: against the wall, against the ceiling or at an angle against the same wall as the shower. The door has 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. The screen has 8mm toughened safety glass and an extension profile can be purchased for surface-mounted piping. Height 2000 mm. 22 mm door seal, magnetic strip and handle included.

DETAILED INFORMATION

Item number	
NOBB	53339720
RSK	7378941
EAN	7330027105789
Stocked article	Yes
Standards and classifications	
EN standard	EN14428
Sunda Hus	Yes
Säker Vatten	Yes
CE marked	Yes
ETIM	EC010038
Product dimensions and weight	
Height (mm)	2000
Width	1460
Width max (mm)	1470
Width min. (mm)	1455
Depth (mm)	800
Depth max. (mm)	810
Depth min. (mm)	790
Glass thickness, door (mm)	6
Glass thickness, fixated wall (mm)	8
Hinge lift height (mm)	4
Floor gap max. (mm)	8
Net weight (kg)	75,3
Left/right model	Vändbar

Material and surface treatment	
Main material	Safety glass, Aluminum
Surface treatment	Anodized
Color	Aluminum
Packaging dimensions and weight	
Package width (m)	1,040
Package height(m)	2,080
Package depth(m)	0,320
Package weight(kg)	79,700

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

Read more on hafa.eu