



## IGLOO PRO DUSCHHÖRN / NISCHDUSCH FROSTAT 90X130

Item number: 1450534

Quickly installed shower corner with a fixed screen and a hinged door in frosted glass. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The door has lifting hinges so that it does not touch the floor when opened and is reversible. The shower rail can be fitted in three ways: against the wall, against the ceiling or at an angle against the same wall as the shower. The door has 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. The screen has 8mm toughened safety glass and an extension profile can be purchased for surface-mounted piping. Height 2000 mm. 22 mm door seal, magnetic strip and handle included.

25 year  
WARRANTY

Quality  
ISO 9001

InstaQuick™  
Patented solution for easy installation and adjustment



Accepterad  
monteringsanvisning  
2021:1

Listad i Svanens  
Husproduktportal



### DETAILED INFORMATION

<b>Item number</b>		<b>Material and surface treatment</b>	
NOBB	53340136	Main material	Safety glass, Aluminum
RSK	7378982	Surface treatment	Anodized
EAN	7330027106199	Glass	Frosted glass
Stocked article	Yes	Color	Aluminum
<b>Standards and classifications</b>		<b>Packaging dimensions and weight</b>	
EN standard	EN14428	Package width (m)	1,340
Sunda Hus	Yes	Package height(m)	2,080
Säker Vatten	Yes	Package depth(m)	0,130
CE marked	Yes	Package weight(kg)	91,500
ETIM	EC010034		
<b>Product dimensions and weight</b>			
Height (mm)	2000		
Width	900		
Width max (mm)	910		
Width min. (mm)	890		
Depth (mm)	1300		
Depth max. (mm)	1310		
Depth min. (mm)	1295		
Width door A	885		
Width of fixed wall (mm)	1285		
Glass thickness, door (mm)	6		
Glass thickness, fixated wall (mm)	8		
Hinge lift height (mm)	4		
Floor gap max. (mm)	8		
Net weight (kg)	87,1/2 (1450534)		
Left/right model	Vändbar		

## CARE INSTRUCTIONS

---

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](https://hafa.eu)