



IGLOO PRO U 80X95

Item number: 1450480

Quickly installed and flexible shower corner with curved doors in clear glass. The special U-shape allows the shower corner to be installed in different ways. It can, for example be installed in a corner, near a window or in the middle of a wall. Perfect for small bathrooms as both doors can be turned inwards against the wall when the shower is not in use. The shower corner is stable with wall profiles in anodised aluminum that can be mounted with screws or glue trays. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The doors have lifting hinges so that it does not touch the floor when opening. See the dimensional sketch for clarification of installation dimensions. 6 mm toughened safety glass. Height 2000 mm. Can be mounted with surface-mounted pipes, 35 mm. Door seal, magnetic strip and handle included.

25 year
WARRANTY

Swedish quality since 1960
Quality

InstaQuick™
Hafa Pat. No. 545554

SundaHus

SÄKER VATTEN
INSTALLATION

Accepterad
monteringsanvisning
2021:1

B

Listad i Svanens
Husproduktportal

EPD

DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	53339606	Main material	Safety glass, Aluminum
RSK	7378929	Surface treatment	Anodized
EAN	7330027105666	Glass	Clear glass
Stocked article	Yes	Color	Aluminum
Standards and classifications		Packaging dimensions and weight	
EN standard	EN14428	Package width (m)	0,985
Sunda Hus	Yes	Package height(m)	2,080
Säker Vatten	Yes	Package depth(m)	0,520
CE marked	Yes	Package weight(kg)	71,600
ETIM	EC010038		
Product dimensions and weight			
Height (mm)	2000		
Width	950		
Depth (mm)	800		
Depth max. (mm)	810		
Depth min. (mm)	790		
Glass thickness (mm)	6		
Hinge lift height (mm)	4		
Floor gap max. (mm)	8		
Net weight (kg)	67,6		
Left/right model	Vändbar		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](https://hafa.eu)