



IGLOO PRO CORNER 70X100

Item number: 1450443

Quickly installed shower corner with hinged doors in frosted glass. When the shower is not in use, the shower doors can be folded against the wall, which frees up space in the bathroom. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The door has lifting hinges so that it does not touch the floor when opened and is reversible. The doors have 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. Height 2000 mm. 22 mm door seal, magnetic strip and handle included.

25 year WARRANTY



Accepterad monteringsanvisning 2021:1

Listad i Svanens Husproduktportal



DETAILED INFORMATION

Item number

NOBB 53339538

RSK 7378922

EAN 7330027105598

Stocked article Yes

Standards and classifications

EN standard EN14428

Sunda Hus Yes

Säker Vatten Yes

CE marked Yes

ETIM EC010034

Product dimensions and weight

Height (mm) 2000

Width 700

Width max (mm) 710

Width min. (mm) 690

Depth (mm) 1000

Depth max. (mm) 1010

Depth min. (mm) 990

Glass thickness (mm) 6

Hinge lift height (mm) 4

Floor gap max. (mm) 8

Net weight (kg) 54,9

Left/right model Vändbar

Material and surface treatment

Main material Safety glass, Aluminum

Surface treatment Anodized

Glass Frosted glass

Color Aluminum

Packaging dimensions and weight

Package width (m) 1,040

Package height(m) 2,080

Package depth(m) 0,130

Package weight(kg) 58,900

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)