



## IGLOO PRO ROUND 90X90

Item number: 1450401

Quickly installed shower corner with curved doors in clear glass. When the shower is not in use the doors are easily turned inwards which frees up space in the bathroom. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. Easily installed and adjusted by one person, InstaQuick®. The shower doors have lifting hinges so that they do not touch the floor when opening and are reversible. 6 mm toughened safety glass. Height 2000 mm. Can be fitted with surface-mounted pipes, cc 35 mm. 22 mm door seal, magnetic strip and handles included.

25 year  
WARRANTY



Accepterad  
monteringsanvisning  
2021:1



Listad i Svanens  
Husproduktportal

EPD

### DETAILED INFORMATION

#### Item number

NOBB	53339315
RSK	7378900
EAN	7330027105376
Stocked article	Yes

#### Standards and classifications

EN standard	EN14428
Sunda Hus	Yes
CE marked	Yes
ETIM	EC010038
BVB id	119335

#### Product dimensions and weight

Height (mm)	2000
Width	900
Width max (mm)	910
Width min. (mm)	890
Depth (mm)	900
Depth max. (mm)	910
Depth min. (mm)	890
Glass thickness (mm)	6
Hinge lift height (mm)	4
Floor gap max. (mm)	8
Net weight (kg)	52
Left/right model	Vändbar

#### Material and surface treatment

Main material	Safety glass, Aluminum
Surface treatment	Anodized
Glass	Clear glass
Color	Aluminum

#### Packaging dimensions and weight

Package width (m)	0,810
Package height(m)	2,080
Package depth(m)	0,175
Package weight(kg)	54,500

## CARE INSTRUCTIONS

---

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)