



IGLOO PRO NICHE 85 F N

Item number: 1450605

Quickly installed straight shower door in frosted glass that is adapted for niche opening and is mounted between fixed walls. The shower door is stable with a wall profile and a profile for the magnetic strip in anodised aluminum. The wall profiles can be mounted with screws or glue trays. The shower door has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The shower door has a lifting hinge so that it does not touch the floor when opening and is reversible. 6 mm toughened safety glass. Height 2000 mm. Can be mounted with surface-mounted pipes, 35 mm. 22 mm trailer strip and handle included. The door can be supplemented with one or more extension profiles to be adapted to the dimensions of the niche.



Accepterad
monteringsanvisning
2021:1

Listad i Svanens
Husproduktportal



DETAILED INFORMATION

Item number

| | |
|-----------------|---------------|
| NOBB | 53340643 |
| RSK | 7330647 |
| EAN | 7330027106700 |
| Stocked article | Yes |

Standards and classifications

| | |
|--------------|----------|
| EN standard | EN14428 |
| Sunda Hus | Yes |
| Säker Vatten | Yes |
| CE marked | Yes |
| ETIM | EC010962 |
| BVB id | 185191 |

Product dimensions and weight

| | |
|------------------------|---------|
| Height (mm) | 2000 |
| Width | 850 |
| Width max (mm) | 870 |
| Width min. (mm) | 830 |
| Depth (mm) | 27 |
| Nische width | 830-870 |
| Glass thickness (mm) | 6 |
| Hinge lift height (mm) | 4 |
| Floor gap max. (mm) | 8 |
| Net weight (kg) | 29,2 |
| Left/right model | Vändbar |

Material and surface treatment

| | |
|-------------------|------------------------|
| Main material | Safety glass, Aluminum |
| Surface treatment | Anodized |
| Glass | Frosted glass |
| Color | Aluminum |

Packaging dimensions and weight

| | |
|--------------------|--------|
| Package width (m) | 0,065 |
| Package height(m) | 2,100 |
| Package depth(m) | 0,900 |
| Package weight(kg) | 30,900 |

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)