



## SHOWER DOOR IGLOO PRO 75 NICHE 730-770MM CLEAR GLASS

Item number: 1450820

Quickly installed straight shower door in clear glass with profiles in black matt or aluminum that is adapted for niche opening and is mounted between fixed walls. The shower door is stable with a wall profile and a profile for the magnetic strip in anodised aluminum. The wall profiles can be mounted with screws or glue trays. The shower door has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The shower door has a lifting hinge so that it does not touch the floor when opening and is reversible. 6 mm toughened safety glass. Height 2000 mm. Can be mounted with surface-mounted pipes, 35 mm. 22 mm trailer strip and handle included. The door can be supplemented with one or more extension profiles to be adapted to the dimensions of the niche.

25 year  
WARRANTY



Listad i Svanens  
Husproduktportal



### DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	60049104	Main material	Safety glass, Aluminum
EAN	7330027149196	Surface treatment	Lacquered
<b>Standards and classifications</b>		Glass	Clear glass
EN standard	EN14428	Color	Black
CE marked	Yes	<b>Packaging dimensions and weight</b>	
ETIM	EC011329	Package width (m)	0,800
BVB id	185191	Package height(m)	2,100
<b>Product dimensions and weight</b>		Package depth(m)	0,065
Height (mm)	2000	Package weight(kg)	26,900
Height min. (mm)	2000		
Width	750		
Width max (mm)	770		
Width min. (mm)	730		
Depth (mm)	27		
Niche width	730-770		
Glass thickness (mm)	6		
Glass thickness, fixated wall (mm)	25.3		
Net weight (kg)	24,9		

## CARE INSTRUCTIONS

---

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)