

# IGLOO PRO SKÄRMVÄGG J KLARGLAS 80

Item number: 1450350

Quickly installed curved shower door in clear glass .Practical shower door that is easily turned inwards when not in use and fits the smaller bathroom. The shower door is stable with a wall profile in anodized aluminum that can be mounted with a screw or glue trays. Easily installed and adjusted by one person, InstaQuick™. The shower door has a lifting hinge so that it does not touch the floor when opening and is reversible. 6 mm toughened safety glass. Height 2000 mm. Can be mounted with surface-mounted pipes, cc 35 mm. 22 mm door seal and handle included. The shower door can be combined with other doors and walls in the IglooPro series.

25 year WARRANTY

Accepterad monteringsanvisning 2021:1

Listad i Svanens Husproduktportal

EPD

## DETAILED INFORMATION

| | |
|---|---|
| **Item number** | |
| NOBB | 53339103 |
| RSK | 7330641 |
| EAN | 7330027105147 |
| Stocked article | Yes |
| **Standards and classifications** | |
| EN standard | EN14428 |
| Sunda Hus | Yes |
| Säker Vatten | Yes |
| CE marked | Yes |
| ETIM | EC010038 |
| BVB id | 119335 |
| EPD HUB id | HUB-2147 |
| **Product dimensions and weight** | |
| Height (mm) | 2000 |
| Width | 800 |
| Width max (mm) | 800 |
| Width min. (mm) | 790 |
| Depth (mm) | 475 |
| Right door width | 810 |
| Glass thickness (mm) | 6 |
| Hinge lift height (mm) | 4 |
| Floor gap max. (mm) | 8 |
| Net weight (kg) | 33,8 |
| Left/right model | Vändbar |

| | |
|---|---|
| **Material and surface treatment** | |
| Main material | Safety glass, Aluminum |
| Surface treatment | Anodized |
| Glass | Clear glass |
| Color | Aluminum |
| **Packaging dimensions and weight** | |
| Package width (m) | 0,985 |
| Package height(m) | 2,080 |
| Package depth(m) | 0,260 |
| Package weight(kg) | 35,800 |

## *CARE INSTRUCTIONS*

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

Read more on hafa.eu