



SHOWER DOOR IGLOO PRO BEND 80 CLEAR BLACK

Item number: 1450325

Quickly installed curved shower door in clear glass. Practical shower door that is easily turned inwards when not in use and fits the smaller bathroom. The shower door is stable with a wall profile in black lacquered aluminum that can be mounted with a screw or glue trays. Easily installed and adjusted by one person, InstaQuick™. The shower door has a lifting hinge so that it does not touch the floor when opening and is reversible. 6 mm toughened safety glass. Height 2000 mm. Can be mounted with surface-mounted pipes, cc 35 mm. 18 mm door seal and handle included.

25 year
WARRANTY



Accepterad
monteringsanvisning
2021:1



Listad i Svanens
Husproduktportal



DETAILED INFORMATION

Item number

NOBB	57295352
RSK	7381722
EAN	7330027115504

Standards and classifications

EN standard	EN14428
Säker Vatten	Yes
CE marked	Yes
ETIM	EC010038
BVB id	164405
EPD HUB id	HUB-2147

Product dimensions and weight

Height (mm)	2000
Width	637
Width max (mm)	647
Width min. (mm)	627
Depth (mm)	137
Glass thickness (mm)	6
Hinge lift height (mm)	4
Floor gap max. (mm)	8
Net weight (kg)	22,3
Left/right model	Vändbar

Material and surface treatment

Main material	Safety glass, Aluminum
Surface treatment	Lacquered
Glass	Clear glass
Color	Black

Packaging dimensions and weight

Package width (m)	0,715
Package height(m)	2,080
Package depth(m)	0,120
Package weight(kg)	24,300

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)