



## IGLOO PRO J + SKÄRMVÄGG FAST FROSTAT 80X130

Item number: 1450469

Quickly installed and extra spacious shower corner in J-shaped design that provides space for double shower sets. The shower corner consists of a J-shaped shower door in clear glass and a straight, fixed shower screen in frosted glass. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The doors have lifting hinges so that they do not touch the floor when opened and are reversible. The shower rail can be mounted in three different ways: against the wall, against the ceiling or at an angle to the same wall as the shower wall is mounted. The door has 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. The screen has 8mm toughened safety glass and an extension profile can be purchased for surface-mounted piping. Height 2000 mm. 22 mm door seal, magnetic strip and handle included.

25 year WARRANTY



Accepterad monteringsanvisning 2021:1



### DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	53339784	Main material	Safety glass, Aluminum
RSK	7378947	Surface treatment	Anodized
EAN	7330027105840	Glass	Clear glass/Frosted
Stocked article	Yes	Color	Aluminum
Standards and classifications		Packaging dimensions and weight	
EN standard	EN14428	Package width (m)	1,340
Sunda Hus	Yes	Package height(m)	2,080
Säker Vatten	Yes	Package depth(m)	0,310
CE marked	Yes	Package weight(kg)	94,900
ETIM	EC010038		
Product dimensions and weight			
Height (mm)	2000		
Width	1760		
Width max (mm)	1770		
Width min. (mm)	1755		
Depth (mm)	800		
Depth max. (mm)	810		
Depth min. (mm)	790		
Glass thickness, door (mm)	6		
Glass thickness, fixated wall (mm)	8		
Hinge lift height (mm)	4		
Floor gap max. (mm)	8		
Net weight (kg)	92,1		
Left/right model	Vändbar		

<sup>1</sup>/<sub>2</sub> (1450469)

## CARE INSTRUCTIONS

---

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)