



IGLOO PRO SKÄRMVÄGG FAST FROSTAT 80

Item number: 1450341

Classic shower screen in frosted glass with aluminum profile against wall and floor that makes the shower screen stable and keeps the water inside. The shower rail can be fitted in three ways: against the wall, against the ceiling or at an angle against the same wall as the shower. The shower screen is reversible so you can choose which wall to install it on. The shower screen can be combined with a shower curtain or with doors in the IglooPro series. Extension profile is available for surface-mounted piping. Mounted with screw or glue. 8 mm toughened safety glass. Height 2000 mm.



Listad i Svanens
Husproduktportal



DETAILED INFORMATION

| Item number | | Material and surface treatment | |
|-------------------------------|---------------|---------------------------------|------------------------|
| NOBB | 53339175 | Main material | Safety glass, Aluminum |
| RSK | 7376770 | Surface treatment | Anodized |
| EAN | 7330027105215 | Glass | Frosted glass |
| Stocked article | Yes | Color | Aluminum |
| Standards and classifications | | Packaging dimensions and weight | |
| EN standard | EN14428 | Package width (m) | 0,840 |
| Sunda Hus | Yes | Package height(m) | 2,080 |
| Säker Vatten | Yes | Package depth(m) | 0,065 |
| CE marked | Yes | Package weight(kg) | 34,800 |
| ETIM | EC010962 | Miscellaneous | |
| Product dimensions and weight | | Corner mounted | |
| Height (mm) | 2000 | | |
| Width | 775 | | |
| Depth (mm) | 21 | | |
| Glass thickness (mm) | 8 | | |
| Net weight (kg) | 32,8 | | |
| Left/right model | Vändbar | | |

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.