

SHOWER DOOR IGLOO PRO STR 90 CLEAR GLASS BLACK

Item number: 1450316

Quickly installed straight shower door in clear glass with prodiles in black matt or aluminum. Practical reversible shower door that is easily turned inwards when not in use and fits the smaller bathroom. The shower door is stable with a wall profile in black lacquered aluminum that can be mounted with a screw or glue trays. Easily installed and adjusted by one person, InstaQuick™. The shower door has a lifting hinge so that it does not touch the floor when opening and is reversible. The shower door can be combined with other doors and screens in the IglooPro series. 6 mm toughened safety glass. Height 2000 mm. Can be mounted with surface-mounted pipes, cc 35 mm. 22 mm door seal and handle included.

25 year WARRANTY

Accepterad monteringsanvisning 2021:1

Listad i Svanens Husproduktportal

EPD

DETAILED INFORMATION

Item number	
NOBB	57295344
RSK	7381721
EAN	7330027115498

Standards and classifications	
EN standard	EN14428
CE marked	Yes
ETIM	EC010962
BVB id	164405
EPD HUB id	HUB-2147

Product dimensions and weight	
Height (mm)	2000
Width	875
Width max (mm)	885
Width min. (mm)	865
Depth (mm)	27
Glass thickness (mm)	6
Hinge lift height (mm)	4
Floor gap max. (mm)	8
Net weight (kg)	30,4
Left/right model	Vändbar

Material and surface treatment	
Main material	Safety glass, Aluminum
Surface treatment	Lacquered
Glass	Clear glass
Color	Black

Packaging dimensions and weight	
Package width (m)	0,940
Package height(m)	2,080
Package depth(m)	0,065
Package weight(kg)	32,400

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

Read more on hafa.eu