



BATHTUB WALL IGLOO PRO

Item number: 1450355

Pivotal bathtub screen with glueable profile in aluminum for wall mounting. 6 mm toughened safety glass. Lifting hinges. Height 1500 mm. Installed against solid ground. Can be fitted with 12 mm surface-mounted pipes cc 35 mm. Extension profile is available for surface-mounted piping. 22 mm door seal included.

25 year WARRANTY



Accepterad monteringsanvisning 2021:1



DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	55966237	Main material	Safety glass, Aluminum
RSK	7377080	Glass	Clear glass
EAN	7330027113708	Color	Aluminum
Standards and classifications		Packaging dimensions and weight	
EN standard	EN14428	Package width (m)	0,870
CE marked	Yes	Package height(m)	1,570
ETIM	EC010179	Package depth(m)	0,055
BVB id	136624	Package weight(kg)	20,300
EPD HUB id	HUB-2147		
Product dimensions and weight			
Height (mm)	1500		
Height min. (mm)	23		
Width	750		
Depth (mm)	21		
Glass thickness (mm)	6		
Hinge lift height (mm)	3		
Net weight (kg)	18,3		
Left/right model	Vändbar		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)