



SHOWER CORNER IGLOO PRO DOOR + WALL CLEAR GLASS 90X100 ALU

Item number: 1450513

Quickly installed shower corner with a fixed screen and a hinged door in clear glass. The shower is stable with wall profiles in black lacquered aluminum that can be mounted with a screw or glue trays. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The door has lifting hinges so that it does not touch the floor when opened and is reversible. The shower rail can be fitted in three ways: against the wall, against the ceiling or at an angle against the same wall as the shower. The door has 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. The screen has 8mm toughened safety glass and an extension profile can be purchased for surface-mounted piping. Height 2000 mm. 22 mm door seal, magnetic strip and handle included.

25 year
WARRANTY



Accepterad
monteringsanvisning
2021:1

Listad i Svanens
Husproduktportal



DETAILED INFORMATION

Item number

NOBB	53339924
RSK	7378961
EAN	7330027105987
Stocked article	Yes

Standards and classifications

EN standard	EN14428
Sunda Hus	Yes
Säker Vatten	Yes
CE marked	Yes
ETIM	EC010034

Product dimensions and weight

Height (mm)	2000
Width	900
Width max (mm)	910
Width min. (mm)	890
Depth (mm)	1000
Depth max. (mm)	1010
Depth min. (mm)	995
Width door A	885
Width of fixed wall (mm)	985
Glass thickness, door (mm)	6
Glass thickness, fixated wall (mm)	8
Hinge lift height (mm)	4
Floor gap max. (mm)	8

Net weight (kg) 71,9/2 (1450513)

Left/right model Vändbar

Material and surface treatment

Main material	Safety glass, Aluminum
Surface treatment	Anodized
Glass	Clear glass
Color	Aluminum

Packaging dimensions and weight

Package width (m)	1,040
Package height(m)	2,080
Package depth(m)	0,130
Package weight(kg)	76,300

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)