



SHOWER CORNER IGLOO PRO DOOR + WALL 70X70 CLEAR GLASS

Item number: 1450800

Quickly installed shower corner with a fixed screen and a hinged door in clear glass. The shower is stable with wall profiles in black lacquered aluminum that can be mounted with a screw or glue trays. It has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The door has lifting hinges so that it does not touch the floor when opened and is reversible. The shower rail can be fitted in three ways: against the wall, against the ceiling or at an angle against the same wall as the shower. The door has 6 mm toughened safety glass and can be mounted with surface-mounted pipes, 35 mm. The screen has 8mm toughened safety glass and an extension profile can be purchased for surface-mounted piping. Height 2000 mm. 22 mm door seal, magnetic strip and handle included.

25 year
WARRANTY

Swedish quality since 1967
Quality

Hafa Pat. No. 308814
InstaQuick™

Listad i Svanens
Husproduktportal



DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	60049108	Main material	Safety glass, Aluminum
EAN	7330027148991	Glass	Clear glass
Standards and classifications		Color	Black
EN standard	EN14428	Packaging dimensions and weight	
CE marked	Yes	Package width (m)	0,740
ETIM	EC010034	Package height(m)	2,080
Product dimensions and weight		Package depth(m)	0,130
Height (mm)	2000	Package weight(kg)	55,800
Width	700		
Width max (mm)	711		
Width min. (mm)	690		
Depth (mm)	700		
Glass thickness, door (mm)	6		
Glass thickness, fixated wall (mm)	8		
Hinge lift height (mm)	4		
Net weight (kg)	51,4		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.