



IGLOO PRO ROUND 90X100

Item number: 1450426

Quickly installed shower corner with curved doors in clear glass. When the shower is not in use the doors are easily turned inwards which frees up space in the bathroom. The shower is stable with wall profiles in anodised aluminum that can be mounted with a screw or glue trays. Easily installed and adjusted by one person, InstaQuick®. The shower doors have lifting hinges so that they do not touch the floor when opening and are reversible. 6 mm toughened safety glass. Height 2000 mm. Can be fitted with surface-mounted pipes, cc 35 mm. 22 mm door seal, magnetic strip and handles included.

25 year
WARRANTY



Accepterad
monteringsanvisning
2021:1



Listad i Svanens
Husproduktportal

EPD

DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	53339402	Main material	Safety glass, Aluminum
RSK	7378909	Surface treatment	Anodized
EAN	7330027105468	Glass	Clear glass
Stocked article	Yes	Color	Aluminum
Standards and classifications		Packaging dimensions and weight	
EN standard	EN14428	Package width (m)	0,915
Sunda Hus	Yes	Package height(m)	2,080
Säker Vatten	Yes	Package depth(m)	0,260
CE marked	Yes	Package weight(kg)	57,900
ETIM	EC010038		
BVB id	119335		
Product dimensions and weight			
Height (mm)	2000		
Width	900		
Width max (mm)	910		
Width min. (mm)	890		
Depth (mm)	1000		
Depth max. (mm)	1010		
Depth min. (mm)	990		
Glass thickness (mm)	6		
Hinge lift height (mm)	4		
Floor gap max. (mm)	8		
Net weight (kg)	53,9		
Left/right model	Vändbar		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](https://hafa.eu)