



IGLOO PRO SKÄRMVÄGG FAST FROSTAT 90

Item number: 1450342

Classic shower screen in frosted glass with aluminum profile against wall and floor that makes the shower screen stable and keeps the water inside. The shower rail can be fitted in three ways: against the wall, against the ceiling or at an angle against the same wall as the shower. The shower screen is reversible so you can choose which wall to install it on. The shower screen can be combined with a shower curtain or with doors in the IglooPro series. Extension profile is available for surface-mounted piping. Mounted with screw or glue. 8 mm toughened safety glass. Height 2000 mm.

25 year
WARRANTY



Listad i Svanens
Husproduktportal



DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	53339186	Main material	Safety glass, Aluminum
RSK	7376771	Surface treatment	Anodized
EAN	7330027105222	Glass	Frosted glass
Stocked article	Yes	Color	Aluminum
Standards and classifications		Packaging dimensions and weight	
EN standard	EN14428	Package width (m)	0,940
Sunda Hus	Yes	Package height(m)	2,080
Säker Vatten	Yes	Package depth(m)	0,065
CE marked	Yes	Package weight(kg)	39,600
ETIM	EC010962	Miscellaneous	
EPD HUB id	HUB-2147		Corner mounted
Product dimensions and weight			
Height (mm)	2000		
Width	875		
Depth (mm)	21		
Glass thickness (mm)	8		
Net weight (kg)	37,6		
Left/right model	Vändbar		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.

[Read more on hafa.eu](#)