



SHOWER DOOR IGLOO PRO 95 NICHE 930-1030MM CLEAR GLASS

Item number: 1450865

Quickly installed straight shower door in clear glass with profiles in black matt or aluminum that is adapted for niche opening and is mounted between fixed walls. The shower door is stable with a wall profile and a profile for the magnetic strip in anodised aluminum. The wall profiles can be mounted with screws or glue trays. The shower door has a patented solution for easy installation and adjustment, Hafa's InstaQuick™. The shower door has a lifting hinge so that it does not touch the floor when opening and is reversible. 6 mm toughened safety glass. Height 2000 mm. Can be mounted with surface-mounted pipes, 35 mm. 22 mm trailer strip and handle included. The door can be supplemented with one or more extension profiles to be adapted to the dimensions of the niche.



DETAILED INFORMATION

Item number		Material and surface treatment	
NOBB	60049129	Main material	Safety glass, Aluminum
EAN	7330027149516	Surface treatment	Anodized
Standards and classifications		Glass	Clear glass
EN standard	EN14428	Color	Aluminum
CE marked	Yes	Packaging dimensions and weight	
ETIM	EC011329	Package width (m)	0,940
Product dimensions and weight		Package height(m)	2,080
Height (mm)	2000	Package depth(m)	0,118
Height min. (mm)	2000	Package weight(kg)	36,700
Width	1010		
Width max (mm)	1030		
Width min. (mm)	990		
Depth (mm)	27		
Niche width	990-1030		
Glass thickness (mm)	6		
Glass thickness, fixated wall (mm)	36.7		
Net weight (kg)	36,2		

CARE INSTRUCTIONS

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.